



Data Sheet
Aegis Series

EL-RG-2.4K

Pharmacy Refrigerator

EL-RG-2.4K

Medical & Pharmacy Refrigerator

GENERAL SPECIFICATIONS

| | |
|----------------------|--|
| Storage Volume | 2.4 cu ft |
| Exterior (W x D x H) | 20.1"x 20.9"x 25.8" / 510.5x530.8x655.32mm |
| Interior (W x D x H) | 15.5" x 15.5" x 16" / 393.7x393.7x406.4mm |
| Insulation | CFC-free, high density insulation |
| Doors | 1 |
| Shelves | 3 |
| Access Port | 0.5" Probe port |
| Leveling Legs | Standard |
| Unit Weight | 88 lbs / 39.9kg |

PERFORMANCE

| | |
|-------------------------------|---|
| Peak Variance | 4.73°C |
| Stability | +/- 2°C |
| Energy Consumption (KWhr/day) | 0.58 |
| Adjustable Set Point Range | 2°C to 8°C |
| Factory Set Point | +4°C |
| Electrical Power/ Current | 120v 60 Hz |
| Building Supply Rating | 15 Amp |
| Power Plug/Cord Length | NEMA 5-15 / 10ft cord |
| Agency Listings | UL/cUL |
| VFC Compliant | Yes |
| Energy Star | Yes |
| Indoor/Outdoor Use | Indoor use only |
| Application Environment | Non-corrosive, non-flammable, non-explosive |
| Ambient Operating Temp. | 25°C to 32°C |

REFRIGERATION

| | |
|----------------------|--|
| Refrigeration System | Vapor compression system, forced-air |
| Compressor | Hermetically sealed compressor |
| Condenser Type | Foamed in |
| Expansion Device | Capillary tube |
| Evaporator Type | Cold wall Evaporator |
| Defrost | Variable (cycle) |
| Refrigerant | R600a (Isobutane)- EPA, SNAP compliant |

CONTROLLER/SYSTEM CONFIGURATION

| | |
|------------------------|-------------------------------------|
| User Interface | Microprocessor with digital display |
| Power Switch | On/Off |
| Controller Type | Digital controller |
| Security | Lockable doors |
| Control Sensor | NTC probe |
| Remote Alarm Terminals | Standard |
| High/Low Alarms | Standard |
| Warranty | 2 years parts & labor |

