

EL-BW-125U

The countertop blanket warmers for labor and delivery rooms, ICU and NICU

- Glass window to view contents inside
- Energy-efficient coated glass door
- Standard lights, UV lamps, with circulation fan
- Digital temperature limiter

SPECIFICATIONS

Inner Chamber Size (W*L*H)mm	500*450*550
Exterior Size	675*580*820
Packing Size	755*672*975
Volume	125L / 4.4 cu ft
Shelf Number	13
Load Per Rack	15kg
Shelf Space	35mm
Power Rating	0.45kW
Current Rating	AC 110V/5.5A
NW/GW (kg)	45/49

FUNCTION

Temperature Range	RT+5 ~ 70 °C
Temperature Resolution Ration	0.1 °C
Temperature Motion	± 0.5 °C
Temperature Uniformity	± 0.8 °C
Factory default setpoint	40 °C

STRUCTURE

Inner Chamber	Cold rolling steel electrostatic
Opter Shell	High quality foam board
Insulation Layer	Mica electrothermal film
Heater	Ø 28mm top (with function of test hole)

CONTROLLER

Temperature Control Mode	PID Intelligent
Temperature Setting Mode	Touch button setting
Temperature Display Mode	Digital temperature: LCD upper row; Setting temperature: the lower row
Timer	0-9999 min (with timing wait function)
Operation function	Fixed temperature operation, timing function, auto stop.
Additional Function	LED Flood light, Sensor deviation correction, temperature overshoot self-tuning, power-off parameter memory
Sensor	PT100
Safety Device	Digital, over temperature sound-light alarm

ACCESSORY

Shelf	2
Shelf frame	4

